

# kubota

## 08 Series

TRACTOR MODEL	L3408DT	L4508DT
DRIVE TYPE	4WD	4WD
ENGINE MODEL	Kubota D1703-M-DI	Kubota V2203-M-DI
ENGINE TYPE	Diesel	Diesel
HP	35hp	45hp
OVERALL LENGTH INC FEL, INC TPL	3960mm	4450mm
OVERALL WIDTH INC FEL	1590mm	1700mm
OVERALL HEIGHT INC ROPS	2350mm	2350mm
HEIGHT TO STEERING WHEEL	1520mm	1520mm
WEIGHT	1150kg + FEL	1365kg + FEL
BATTERY VOLTS	12V	12V
WHEEL BASE	1610mm	1845mm
MINIMUM GROUND CLEARANCE	310mm	330mm
GROUND POLARITY	Negative	Negative
CYLINDERS	3	4
CYLINDER SLEEVE	Yes	Yes
DISPLACEMENT	1647cc	2197cc
GEARBOX	Manual	Manual
FORWARD SPEEDS	8	8
REVERSE SPEEDS	4	4
BRAKE TYPE	Wet Disc	Wet Disc
CLUTCH TYPE	Dry Single	Dry Single
LUBRICATION	Forced Lubrication by Trichiodal Pump	Forced Lubrication by Trichiodal Pump
COOLING	Water with Pressurised Radiator	Water with Pressurised Radiator
REAR DIFFERENTIAL LOCK	Yes	Yes
PTO SPEED 1	540rpm	540rpm
PTO SPEED 2	750rpm	750rpm
PTO DIRECTION	Clockwise	Clockwise
FUEL CAPACITY	34L	42L
ENGINE OIL	7L	7.6L
TRANSMISSION/HYDRAULIC	40L	40L
FRONT AXLE GEAR CASE	6L	6.5L
FRONT TYRE SIZE - AGRICULTURAL	8 X 16	8 X 18
REAR TYRE SIZE - AGRICULTURAL	12.4 X 24	13.6 X 26

FRONT END LOADER MODEL	X35	X45
SWL + 100KG BALLAST	320kg	420kg
BUCKET WIDTH	1590mm	1700mm
BUCKET HEIGHT	335mm	335mm
LIFT HEIGHT	2170mm	2220mm
DUMP CLEARANCE	1740mm	1830mm
CROWD ANGLE	30°	30°
DUMP ANGLE	45°	45°
FEL WEIGHT	400kg	460kg

Note: These figures are intended as a guideline only. Individual tractors may vary.