

kubota

L1 Series

TRACTOR MODEL	L1-18DT	L1-20DT	L1-22DT	L1-24DT
DRIVE TYPE	4WD	4WD	4WD	4WD
ENGINE MODEL	Kubota D1302 DI	Kubota D1402 DI	Kubota D1462 DI-L	Kubota D1462 DI
ENGINE TYPE	Diesel	Diesel	Diesel	Diesel
HP	22hp	24hp	26hp	28hp
OVERALL LENGTH INC FEL, EX TPL	3400mm	3400mm	3500mm	3500mm
OVERALL WIDTH INC FEL	1340mm	1340mm	1400mm	1570mm
OVERALL HEIGHT INC ROPS	2160mm	2160mm	2200mm	2200mm
HEIGHT TO STEERING WHEEL	1400mm	1400mm	1400mm	1400mm
WEIGHT	975kg + FEL	980kg + FEL	1010kg + FEL	1070kg + FEL
BATTERY VOLTS	12V	12V	12V	12V
WHEEL BASE	1520mm	1520mm	1540mm	1540mm
MINIMUM GROUND CLEARANCE	275mm	275mm	275mm	315mm
GROUND POLARITY	Negative	Negative	Negative	Negative
CREEPER	Yes	Yes	Yes	Yes
CYLINDERS	3	3	3	3
CYLINDER SLEEVE	Yes	Yes	Yes	Yes
DISPLACEMENT	1299cc	1395cc	1462cc	1462cc
GEARBOX	Shuttle Shift	Shuttle Shift	Shuttle Shift	Shuttle Shift
FORWARD SPEEDS	16	16	16	16
REVERSE SPEEDS	16	16	16	16
BRAKE TYPE	Wet Disc	Wet Disc	Wet Disc	Wet Disc
CLUTCH TYPE	Dry Single	Dry Single	Dry Single	Dry Single
LUBRICATION	Forced Lubrication by Trichiodal Pump	Forced Lubrication by Trichiodal Pump	Forced Lubrication by Trichiodal Pump	Forced Lubrication by Trichiodal Pump
COOLING	Water with Pressurised Radiator	Water with Pressurised Radiator	Water with Pressurised Radiator	Water with Pressurised Radiator
REAR DIFFERENTIAL LOCK	Yes	Yes	Yes	Yes
PTO SPEED 1	540rpm	540rpm	540rpm	540rpm
PTO SPEED 2	770rpm	770rpm	770rpm	770rpm
PTO SPEED 3	940rpm	940rpm	940rpm	940rpm
PTO SPEED 4	1250rpm	1250rpm	1250rpm	1250rpm
PTO DIRECTION	Clockwise	Clockwise	Clockwise	Clockwise
FUEL CAPACITY	29L	29L	29L	29L
ENGINE OIL	5.7L	5.7L	5.7L	5.7L
TRANSMISSION/HYDRAULIC	26L	26L	26L	28.5L
FRONT AXLE GEAR CASE	6L	6.5L	6.5L	6.5L
FRONT TYRE SIZE – AGRICULTURAL	6 X 14	6 X 14	6 X 14	7 X 16
REAR TYRE SIZE – AGRICULTURAL	8.3 X 24	9.5 X 22	9.5 X 24	11.2 X 24

FRONT END LOADER MODEL	X35	X35	X35	X35
SWL + 100KG BALLAST	300kg	300kg	300kg	300kg
BUCKET CAPACITY (VOLUME)	0.12m ³	0.12m ³	0.12m ³	0.12m ³
BUCKET WIDTH	1260mm	1260mm	1400mm	1500mm
BUCKET HEIGHT	350mm	350mm	350mm	350mm
LIFT HEIGHT	2100mm	2100mm	2100mm	2100mm
DUMP CLEARANCE	1800mm	1800mm	1800mm	1800mm
CROWD ANGLE	15°	15°	15°	15°
DUMP ANGLE	30°	30°	30°	30°
FEL WEIGHT	380kg	380kg	380kg	380kg

Note: These figures are intended as a guideline only. Individual tractors may vary.