

# FARMTRAC



FT30 28.5hp

**sota**tractors  
EXCLUSIVE AUSTRALIAN DISTRIBUTOR



# sotatractors

EXCLUSIVE AUSTRALIAN DISTRIBUTOR

**VIC** 200 Mahoneys Rd, Thomastown 3074 P 03 9462 3488

**NSW** 19-21 Smith St, Emu Plains 2750 P 02 4735 5931

**QLD** 2 Fortune St, Geebung 4034 P 07 3865 6755

**TOLL FREE 1300 767 297**

## FARMTRAC FT30 28.5hp

### ENGINE

Engine brand	Mitsubishi MV S3L2
Engine type	Natural aspirated
Number of cylinders	3
Capacity	1318cc
Engine rated power	28.5hp @ 2800rpm
Maximum torque	80.5Nm @ 1800rpm
Fuel tank capacity	24L

### DIMENSIONS

Tractor length	2465mm (without TPL)
Tractor length with FEL	3680mm
Tractor width	1200mm
Tractor height	1960mm
Clearance	310mm
Front tyres (Ag)	6 x 12
Rear tyres (Ag)	8.3 x 20
Optional Industrial Tyres	23 x 8.50-12/33 x 15.5-16.5
Optional Turf Tyres	23 x 8.50-12/33 x 15.5-16.5

### WEIGHTS

Tractor weight	680kg
Loader weight	320kg
Total weight	1000kg

### DRIVE

Clutch	Single
Clutch control	Straddle
No. of gears	9F 3R
Steering	Power Steering
Mechanical reverse	With clutch – mechanical
Differential lock	Yes
Minimum speed	1.3 km/h
Maximum speed	20 km/h
PTO horsepower	21
PTO	540/540E

### BRAKES

Working type	Oil immersed
Parking control	Hand lever actuation

### HYDRAULICS

Pump oil flow	37 (21 + 16) L/min
Working pressure	180 bar
No. of hydraulic remotes	2
TPL category	I
Maximum lifting capacity	750kg

### HITCHES

Drawbar	Swinging
---------	----------

### FRONT END LOADER

Model	Farmtrac 6030
Bucket type	4-in-1
Safe working load	360kg
Max. lift height to pivot pins	2170mm
Clearance w/ attach. dump	1680mm
Maximum dump angle	45°
Maximum rollback angle	43°
Bucket width	1200mm
Bucket L x W x H (mm)	1200 x 450 x 425
Raising time (w/out load)	2.7 secs (full height)
Lowering time (w/out load)	2.05 secs
Attachment rollback time	2 secs
Attachment dumping time	2.65 secs

For more information on this model, visit [www.sotatractors.com](http://www.sotatractors.com)

 **MITSUBISHI**®

