

# APOLLO TRACTORS

## MODEL 704 70HP 4WD

### ENGINE

|                    |                          |
|--------------------|--------------------------|
| Engine model       | CHANGFA CF3C70Z-T2 Turbo |
| Engine type        | Diesel                   |
| Engine gross power | 70hp 51.5kW              |
| PTO power          | 60hp 44kW                |
| No. of cylinders   | 4                        |
| Total displacement | 2835cc                   |
| Rated speed        | 2400rpm                  |
| Battery            | 12v 80ah                 |
| Alternator         | 14v 750w                 |
| Fuel tank capacity | 75L                      |

### DRIVE

4 x 4

### TRANSMISSION

Synchro shuttle shift 16F, 16R

### STEERING

Power steering

### BRAKES

Wet disc dual plate

### CLUTCH

10" dual stage dry clutch

### PTO

540 / 1000 rpm

### HYDRAULICS

Hydraulic remotes

Dual

Lift control type

Position and float with hydraulic down pressure

Total hydraulic flow

43.5 L/m

TPL

Cat 2

Lift capacity at 610mm

1450kg (behind lift point)

### DIMENSIONS

|                       |                                  |
|-----------------------|----------------------------------|
| Overall length        | 5100mm                           |
| Overall width         | 1900mm (min tread)               |
| Overall height        | 2620mm                           |
| Min. ground clearance | 373mm                            |
| Min. turning radius   | 3400mm (with brake, without 4WD) |
| Weight with loader    | 3280kg – 3500kg                  |

### FRONT LOADER

|                             |                                  |
|-----------------------------|----------------------------------|
| Model                       | X70                              |
| Bucket type                 | 4-in-1 (standard), quick release |
| Loader type                 | Quick release, Euro hitch        |
| Max. lift height            | 2650mm (from pivot pin)          |
| Clearance                   | 1820mm (with attachment dump)    |
| Max. dump angle             | 60° (level from)                 |
| Max. rollback angle         | 30°                              |
| Bucket width                | 1700mm                           |
| Safe working load (SWL)     | 800kg                            |
| Raising time to full height | 8 sec (without load)             |
| Lowering time (powerdown)   | 6 sec (without load)             |
| Attachment rollback time    | 2 sec                            |
| Attachment dumping time     | 3 sec                            |

### OPTIONAL ATTACHMENTS

X70 Pallet fork  
X70 Bale fork

**sotatractors.com**

EXCLUSIVE AUSTRALIAN DISTRIBUTOR

**PHONE TOLL FREE: 1300 767 297**

200 MAHONEYS RD, THOMASTOWN VIC PH: 03 9462 3488  
19-21 SMITH ST, EMU PLAINS NSW PH: 02 4735 5931  
70 TELFORD ST, VIRGINIA QLD PH: 07 3865 6755

Please note photos are representative only. Specifications may change without notice.  
Stock is subject to availability. All information is correct at time of printing.

