

# kubota

## 02 Series

TRACTOR MODEL	L1802DT	L2002DT	L2202DT	L2402DT
DRIVE TYPE	4WD	4WD	4WD	4WD
ENGINE MODEL	Kubota D1102	Kubota D1302	Kubota D1402L	Kubota D1402
ENGINE TYPE	Diesel	Diesel	Diesel	Diesel
HP	22hp	24hp	26hp	28hp
OVERALL LENGTH INC FEL, EX TPL	3400mm	3430mm	3510mm	3550mm
OVERALL WIDTH INC FEL	1320mm	1320mm	1340mm	1570mm
OVERALL HEIGHT INC ROPS	2240mm	2240mm	2270mm	2270mm
HEIGHT TO STEERING WHEEL	1330mm	1330mm	1360mm	1500mm
WEIGHT	900kg + FEL	910kg + FEL	940kg + FEL	1015kg + FEL
BATTERY VOLTS	12V	12V	12V	12V
WHEEL BASE	1500mm	1500mm	1550mm	1580mm
MINIMUM GROUND CLEARANCE	315mm	315mm	315mm	345mm
GROUND POLARITY	Negative	Negative	Negative	Negative
CREEPER	Yes	Yes	Yes	Yes
CYLINDERS	3	3	3	3
CYLINDER SLEEVE	Yes	Yes	Yes	Yes
DISPLACEMENT	1115cc	1299cc	1395cc	1395cc
GEARBOX	Manual	Manual	Manual	Manual
FORWARD SPEEDS	16	16	16	16
REVERSE SPEEDS	4	4	4	4
BRAKE TYPE	Wet Disc	Wet Disc	Wet Disc	Wet Disc
CLUTCH TYPE	Dry Single	Dry Single	Dry Single	Dry Single
LUBRICATION	Forced Lubrication by Trichiodal Pump	Forced Lubrication by Trichiodal Pump	Forced Lubrication by Trichiodal Pump	Forced Lubrication by Trichiodal Pump
COOLING	Water with Pressurised Radiator	Water with Pressurised Radiator	Water with Pressurised Radiator	Water with Pressurised Radiator
REAR DIFFERENTIAL LOCK	Yes	Yes	Yes	Yes
PTO SPEED 1	540rpm	540rpm	540rpm	540rpm
PTO SPEED 2	770rpm	770rpm	770rpm	770rpm
PTO SPEED 3	940rpm	940rpm	940rpm	940rpm
PTO SPEED 4	1250rpm	1250rpm	1250rpm	1250rpm
PTO DIRECTION	Clockwise	Clockwise	Clockwise	Clockwise
FUEL CAPACITY	14.3L	14.3L	14.3L	18.2L
ENGINE OIL	5L	5.7L	5.7L	5.7L
TRANSMISSION/HYDRAULIC	26L	26L	28.5L	28.5L
FRONT AXLE GEAR CASE	5.8L	5.8L	6L	6.5L
FRONT TYRE SIZE – AGRICULTURAL	6 X 14	6 X 14	6 X 14	7 X 16
REAR TYRE SIZE – AGRICULTURAL	8.3 X 22	9.5 X 22	9.5 X 24	11.2 X 24
FRONT TYRE SIZE – TURF	6 X 14	6 X 14	6 X 14	7 X 16
REAR TYRE SIZE – TURF	8.3 X 22	9.5 X 22	9.5 X 24	11.2 X 24
<b>FRONT END LOADER MODEL</b>	<b>X35</b>	<b>X35</b>	<b>X35</b>	<b>X35</b>
SWL + 100KG BALLAST	300kg	300kg	300kg	300kg
BUCKET CAPACITY (VOLUME)	0.12m <sup>3</sup>	0.12m <sup>3</sup>	0.12m <sup>3</sup>	0.12m <sup>3</sup>
BUCKET WIDTH	1260mm	1260mm	1260mm	1500mm
BUCKET HEIGHT	350mm	350mm	350mm	350mm
LIFT HEIGHT	2100mm	2100mm	2100mm	2100mm
DUMP CLEARANCE	1800mm	1800mm	1800mm	1800mm
CROWD ANGLE	15°	15°	15°	15°
DUMP ANGLE	30°	30°	30°	30°
FEL WEIGHT	380kg	380kg	380kg	380kg

Note: These figures are intended as a guideline only. Individual tractors may vary.